



Materials: 4140 Flame Hardened to Rc 56-62

Tolerances: Screw Holes: +/-0.25

Catalog Number	NAAMS Code		W	L	Holes	A	B	C	D	E	F
	Drilled	Un-drilled									
KPSG30-75-200F	-	-	75	200	3	100	-	-	175	55	40
KPSG30-75-250F	-	-		250		125	-	-	225		
KPSG30-75-315F	-	-		315	5	90	158	225	290		
KPSG30-75-350F	-	-		350		100	175	250	325		
KPSG30-75-400F	-	-		400		115	200	285	375		
KPSG30-75-450F	-	-		450		125	225	325	425		
KPSG30-100-200F	R211020	R221020	100	200	3	100			175	80	55
KPSG30-100-250F	R211025	R221025		250	4	90		160	225		
KPSG30-100-315F	R211031	R221031		315	5	90	158	225	290		
KPSG30-100-350F	R211035	R221035		350		100	175	250	325		
KPSG30-100-400F	R211040	R221040		400		115	200	285	375		
KPSG30-100-450F	R211045	R221045		450		125	225	325	425		
KPSG30-125-200F	R211220	R221220	125	200	3	100			175	105	65
KPSG30-125-250F	R211225	R221225		250	4	90		160	225		
KPSG30-125-315F	R211231	R221231		315	5	90	158	225	290		
KPSG30-125-350F	R211235	R221235		350		100	175	250	325		
KPSG30-125-400F	R211240	R221240		400		115	200	285	375		
KPSG30-125-450F	R211245	R221245		450		125	225	325	425		
KPSG30-150-200F	R211520	R221520	150	200	3	100			175	130	65
KPSG30-150-250F	R211525	R221525		250	4	90		160	225		
KPSG30-150-315F	R211531	R221531		315	5	90	158	225	290		
KPSG30-150-350F	R211535	R221535		350		100	175	250	325		
KPSG30-150-400F	R211540	R221540		400		115	200	285	375		
KPSG30-150-450F	R211545	R221545		450		125	225	325	425		

Ordering Note: For no holes, add an "N" suffix to the end of the catalog number.