



**Cress Mfg. Co.**

**Telephone** Sales 775-884-2777 or 800-423-4584

**Fax** 775-884-2991

From Mexico call 001-800-419-1139

**Postal address**

4736 Convair Dr., Carson City, NV 89706

**Email:** [info@cressmfg.com](mailto:info@cressmfg.com)

## ITEM # C1228DW/PM3T

**Draw Units:** These models are equipped with a stainless steel fan and motor for forced convection temperature uniformity.

**Uses:** These furnaces are designed for general use in the shop, laboratory or factory where temperatures from 300-1250°F.  $\pm 10^\circ\text{F}$  are required. They are used for such purposes as tempering, annealing and stress relieving. 2000°F maximum temperature option is available for all models at additional cost.

**Temperature controls:** Auto tuning microprocessor-based controller and solid



[+ more](#)

### Specifications

|                       |       |
|-----------------------|-------|
| <b>Chamber Width</b>  | 12 in |
| <b>Chamber Length</b> | 17 in |
| <b>Chamber Height</b> | 8 in  |
| <b>Overall Width</b>  | 25 in |

|                                      |  |
|--------------------------------------|--|
| <b>Overall Length</b>                | 43 in  |
| <b>Overall Height</b>                | 28 in  |
| <b>Max. Intermittent Temperature</b> | 1250 °F  |
| <b>Max. Continuous Temperature</b>   | 1000 °F  |
| <b>Input Power</b>                   | 3.5 kW   |
| <b>Weight</b>                        | 400 lb   |
| <b>Options</b>                       | High limit controls<br>Stands and quench tanks |